



HSK-C2

Smart Home Security Kit

HSK-C2 is a smart home security kit including 720P Smart IP Camera, Door Sensor, PIR sensor and remote controller. All devices can connect wirelessly through RF (Radio Frequency) and there is useful alarm video linkage function.

With the help of IP Cameras, user can monitor his home through cellphone. User can set arming and disarming remotely in cellphone or remote controller. Once any alarm exists from door sensor or PIR sensor, it will trigger camera to take snapshot and video. User can receive push notification and check the videos & snapshots by one click.

Compared to traditional alarm system, Ansee Smart Home security system is more useful and secure.

What devices include in this kit?



Smart IP Camera (AX-360)* 2



PIR Motion Detector (DSW-04A) * 1



Door Sensor (TM-01A) * 1



Wireless Remote Controller (RC-915) * 1

Specifications

Model Name	AX360(Smart IP Camera)	
Image Sensor	Sensor	1.3MP CMOS Sensor
	Lens	f=3.6mm, F=2.0
	Angle	70 degree
Video	Video Format	PAL & NTSC
	FPS	25
	Resolution	1280*720, 640*360
	Video output	H.264 dual stream
	White Balance	Auto
	Backlight Compensation	Auto
	IR Distance	Around 10M
Audio	Input/Output	Embedded Microphone and Loudspeaker
	Audio Compression	SPEEX (8KHz or 16KHz)
Network	Wi-Fi	Supports IEEE 802.11b/g/n protocol, Supports wireless security standards: WEP (40bit/ 128bit), WPA (AES), WPA2 (AES),OPEN
Alarm	Wireless Alarm Input	915MHZ/FSK Two-way;Valid Distance \geq 30M (open area); Max. 32 channels
	PIR Motion Detection	High Sensitivity, valid 6m distance, valid angle 60 degree
	Alarm File Format	JPG
	Alarm Alert	APP Push
Device Working Status Indication	Network disconnected	Yellow LED @ Normal On
	Network Setting in process	Yellow LED @ Slow Flash
	Arming	Red LED @ Normal On
	Disarming	Green LED @ Normal On
	RF Delivering Data	Green LED @ Fast Flash
	Watching Real-time Video	Red & Green LED @ Slow Flash
Hardware Interface	Power	5V 1A DC or Micro USB port,Power Consumption \leq 5W
	Reset	1
	Micro SD Card Port	2.0 @Max. 32G
Working Environment	Temperature	-5°C ~40°C
	Humidity	35% ~45%
	Storage Temperature	-40°C ~70°C
General Info.	Measurement (L*W*H)	104*65*41mm
	Net Weight	0.3KG

Model Name	DSW-04A(Infrared Detector)
Working Voltage	9V 6F22 battery
Alarm Current	≤ 30mA
Standby Current	≤ 25uA
RF Distance	≥ 30M (open area)
Mounting Type	Wall Mounting
Install Height	2.2M
Detection Angle	110° (15° for curtain type)
Detection Range	8~12m(25℃)
Radio Frequency	915MHz/FSK
Measurement	107*58*42 mm

Model Name	TM-01A(Door Sensor Detector)
Working Voltage	1.5V(1.5V AA battery)
Battery Life	About 12 months in normal working mode
Alarm Current	≤ 70mA
Standby Current	≤ 40uA
RF Distance	≥ 30M (open area)
Alarm Format	Remote alarm (connect alarm host through RF)
Radio Frequency	915MHz/FSK
Measurement	70*50*20mm

Model Name	RC-915(Wiless Remote Controller)
Color	White
Material	ABS
Working Voltage	3V CR2302 Button Battery
Working Current	≤ 70mA
Standby Current	≤ 1uA
RF Distance	≥ 30M(in open area)
Radio Frequency	915MHz/FSK
Measurement	70mmx38mmx16mm
N.W	20g
Working Temperature	-10℃ -50℃
Working Humidity	10%~95% RH

Ansee Co. Ltd

Add: Building A, GuanLong First Industry Park,
XiLi Town, NanShan District, Shenzhen, China
(518055)

Tel: 0755-86521099/86522966

Fax: 0755-26984949

Email: sales@anseetec.com

Web: www.anseetec.com

© Copyright 2016. * All Rights Reserved*Design and specifications are subject to change without notice.